

Date: 17.09.2024

CCCPL/KW/Env.Statement/2023-24/01

To
The Member Secretary,
Karnataka State Pollution Control Board,
49, 4th& 5th floor,
Parisara Bhavana, Church Street,
Bangalore – 560 001.

Sub: Submission of Environmental Statement Report in "Form V" for the year 2023-24 of Integrated Cement & Captive Power Plant of Chettinad Cement Corporation Private Limited located at Kallur & Sangem K Villages, Chincholi Taluk, Kalaburagi District, Karnataka, under Environment (Protection) Rules, 1986.

Dear Sir,

As mentioned in the above cited subject matter, we are here by submitting the "Environmental Statement Report" FY 2023-24 in the prescribed format (Form V) under Environment (Protection) Rules, 1986 pertaining to our Integrated Cement & Captive Power Plant located at Kallur & Sangem K Villages, Chincholi Taluk, Kalaburagi District, Karnataka.

Kindly acknowledge the receipt of the same.

Yours faithfully,

For Chettinad Cement Corporation Private Limited

K Saikumar Unit Head

Copy to: Environmental officer, Karnataka State Pollution Control Board, Plot No 12/2, Sy.No 19/P, Mansafdar Layout, MG Road, Santraswadi, Kalburagi -585 101

Chettinad Cement Corporation Private Limited

Kallur Works, Sangam K Village Garagapalli Post, Chandapur (SO) Chincholi (TK), Kalaburagi (Gulbarga) (DT) Karnataka, Pin - 585305, India T - 08475 - 295607 E - kallur@chettinadcement.com CIN: U93090TN1962PLC004947 **Head Office**Meyyammai Building, 17/35,

Gandhi Nagar, 2nd Main Road,

Adyar, Chennai - 600020

Tel +91 44 421 9955, 28292727

F +91 44 4309 0202, 2829 1558

E:info@chettinadcement.com www.chettinadcement.com



ENVIRONMENTAL STATEMENT REPORT

FY 2023-2024

PROJECT: INTEGRATED CEMENT PLANT 2.5 MTPA, CAPTIVE POWER PLANT-30 MW and WHR 7.0 MW



Lessee

M/s.Chettinad Cement Corporation Pvt Ltd.

Unit: Kallur works

Sangem K Village, Garagapalli Post Chandapur (S.O), Chincholi Taluka,

Dist: Kalaburagi, Karnataka-585305



CONTENTS

S.No		Page. No
СНАРТЕ	R -1	
PART-A	Form-V	01
PART-B	Water Consumption	02
PART-B	Raw material consumption per ton of cement	02
PART-C	Pollution discharged to Environment/Unit of Output	03
PART-D	Hazardous wastes	05
PART-E	Solid Wastes	06
PART-F	Quantum of Hazardous, Solid Wastes and its disposal practice	06
PART-G	Impact pollution abatement measures taken & Modifications	
	for Energy conservation and Better Environment	07
PART-H	Additional measures /Proposal Modifications for Energy	Ž-
	conservation and Better Environment, Afforestation	08
PART-I	Other Particulars for improving the quality of the Environment	08

FORM - V

(See Rule 14) of Environment (Protection) Rules, 1986)

Environmental Statement for the Financial Year ending the 31st March 2024

PART - A

(i)	Name and address of the owner /occupier of the industry operation or process.	••	M.A.M.R. Muthiah Chettinad Cement Corporation Pvt Ltd, Kallur Limestone Mine, Kallur Village, Chincholi Taluk, Kalaburagi District, Karnataka. Pincode: 585 305	
(ii)	Industry category Primary (STC Code) Secondary (SIC Code)		Red Large 1007- Cement	
(iii)	Production Capacity	•••	Clinker -: 2.0 Million Tons Per Annum (MTPA) Cement -: 2.5 Million Tons Per Annum (MTPA) Power -: 30 MW WHRB -: 7 MW Solar -: 3 MW Power	
(iv)	Year of Establishment	••	2012	
(v)	Date of Last Environmental Statement submitted	•	20.09.2023	

<u>PART – B</u>

Water and Raw Material Consumption

(i) Water Consumption m³/day:

Description	During the Previous Financial Year (2022-2023)	During the Current Financial Year (2023-2024)	
a) Process & Cooling	327.871	347.96	
b) Domestic	161.334	172.522	

Name of the Product		Process water consumption (m³) per unit (MT/MW) of Product Output		
		During the Previous Financial Year (2022-2023)	During the Current Financial Year (2023-2024)	
Cement (m³/MT)		0.0258	0.02448	
Power	(m ³ / MWH)	0.250	0.3330	
WHR	(m ³ /MWH)	0.312	0.2999	

(ii) Raw Material Consumption

a. Cement Plant:

N	ame of the Raw Material	Name of the	Consumption of Raw Material (metric ton) per unit (metric ton) of Output	
		Product	Financial Year Financial Yea	
1	Lime stone		(2022-2023) 1.1059	(2023-2024) 1.0733
2	Laterite		0.0780	0.0692
3	Iron Ore		0.0092	0.0097
4	Red Mud	Cement	0.0025	0
5	Felldspar		0.0017	0.0014
	Fuel – Coal		0.0569	0.0410
6	Petcoke		0.0280	0.0383
7	AFR		0.0099	0.0138
8	Gypsum		0.0284	0.0504
9	Fly Ash		0.136	0.1472
10	HGFA from CPP		0.0053	0.0102

b. Power Plant

1	Name of the Raw	Name of the	Consumption of Raw Material (metric ton) per MW of Output	
	Material	Product	During the Previous Financial Year (2022-2023) During the Current Financial Year (2023-2024)	
1	Fuel - Coal	Power	0.70	0.84

PART - C

Pollution Discharged to Environment / Unit of output (Parameter as specified in the Consent issued)

a. Cement Plant:

Water				
Pollutant	Concentrations of Pollutants in Discharges (Mass/volume) mg/litre	Standards in mg/litre	Percentage of variation from prescribed standards with reasons	
pH Value	7.31	6.5 to 9.0	Within prescribed limits	
BOD	8.74	10	Within prescribed limits	
COD	32	50	Within prescribed limits	
TSS	12.15	20	Within prescribed limits	
Ammonical				
Nitrogen as NH4	0.63	5	Within prescribed limits	
Total Nitrogen	1.58	10	Within prescribed limits	
Fecal coliform	24.38	<100	Within prescribed limits	

Stack gas Quality				
Pollutant	Avg Concentrations of Pollutants in Discharges (Mass/volume) mg/Nm³	Standards in mg/Nm³	Percentage of variation from prescribed standards with reasons	
Kiln stack				
PM	19.7	30	Within prescribed limits	
\$O ₂	17.6	100	Within prescribed limits	
NO _x	367.8	800	Within prescribed limits	
Coal Mill stack				
PM	17.6	30	Within prescribed limits	
Cement Mill stac] 30		



PM	19.3	30	Within prescribed limits		
Cooler stack	Cooler stack				
PM	21.26	30	Within prescribed limits		

Ambient Air G	Ambient Air Quality				
Pollutant	Concentrations of Pollutants in Discharges (Mass/volume) µg/m³	Annual Avg in µg/m³	Percentage of variation from prescribed standards with reasons		
Core zone- Pl	ant				
PM ₁₀	58.3	60	Within Prescribed limits		
PM _{2.5}	22.73	40	Within Prescribed limits		
\$O ₂	13.0	50	Within Prescribed limits		
NO _x	20.88	40	Within Prescribed limits		
Near Captive	Power Plant				
PM ₁₀	59.20	60	Within Prescribed limits		
PM 2.5	22.43	40	Within Prescribed limits		
SO ₂	12.67	50	Within Prescribed limits		
NO _x	20.53	40	Within Prescribed limits		
Buffer Zone					
Mines					
PM ₁₀	58.07	60	Within Prescribed limits		
PM _{2.5}	23.25	40	Within Prescribed limits		
SO ₂	11.75	50	Within Prescribed limits		
NO _x	17.80	40	Within Prescribed limits		
Miryan					
PM ₁₀	57.05	60	Within Prescribed limits		
PM _{2.5}	20.45	40	Within Prescribed limits		
SO ₂	11.48	50	Within Prescribed limits		
NO _x	19.02	40	Within Prescribed limits		
Polkampalli					
PM ₁₀	56.17	60	Within Prescribed limits		
PM 2.5	20.23	40	Within Prescribed limits		
SO ₂	9.90	50	Within Prescribed limits		
NO _x	17.75	40	Within Prescribed limits		
Bhaktampalli					
PM ₁₀	57.55	60	Within Prescribed limits		
PM 2.5	20.53	40	Within Prescribed limits		
SO ₂	11.13	50	Within Prescribed limits		
NO _x	18.97	40	Within Prescribed limits		
Sangam					
PM ₁₀	55.90	60	Within Prescribed limits		
PM 2.5	19.57	40	Within Prescribed limits		
SO2	10.08	50	Within Prescribed limits		
NOx	18.23	40	Within Prescribed limits		



Kallur			
PM 10	56.93	60	Within Prescribed limits
PM 2.5	21.03	40	Within Prescribed limits
SO2	11.23	50	Within Prescribed limits
NOx	18.27	40	Within Prescribed limits

B.Power Plant:

Pollutants	Concentrations of Pollutants in Discharges (Mass/volume) mg/litre Except pH	Standards in mg/litre	Percentage of variation from prescribed standards with reasons
(a) Water			
рН	8.04	5.5 to 9.0	Within prescribed limits
TDS	940	2100	Within prescribed limits
TSS	9.23	100	Within prescribed limits
Chlorides	189.75	1000	Within prescribed limits
Sulphates	46.95	1000	Within prescribed limits
Dissolved Phosphates (as P)	<1.0	5.0	Within prescribed limits
(b) Air			
Pollutant	Concentrations of Pollutants in Discharges (Mass/volume) mg/Nm³	Standards	Percentage of variation from prescribed standards with reasons
PM	20.7	50	Within prescribed limits
SO2	368.8	600	Within prescribed limits
NOx	180.6	300	Within prescribed limits

PART - D

Hazardous Wastes

(Hazardous and Other Wastes (Management and Transboundary Movement) Rules, 2016)

Hazardous Waste		Total Quantity Generated in KL		
		During the Previous Financial Year (2022-2023)	During the Current Financial Year (2023-2024)	
(a)	From Process	1.3 (used for in-house	2.02 (0.5 KL utilized in-	
	Used Oil (Category No 5.1)	lubrication)	house lubrication)	
(b)	From Pollution Control	NIL	Nil	



Facilities	

Hazardous Waste Category	Quantity Received In MT	Quantity Co- processed In MT
28.1 (Solid)	93.69	93.69
28.1 (Liquid)	624.38	624.38
36.1	1391.6	1391.6
28.6	2594.92	2594.92
28.3	419.1	419.1
35.3	438.58	438.58
5.2	569.13	569.13
21.1	257.63	202.76
28.5	145.27	145.27
Non Hazardous Waste		
RDF	18986.72	19263.86
Plastic/MLP	337.87	546.29
Dolochar	0	22.67
Bio Fuel	3031.24	5112.59
Other Waste	47.6	47.6

<u>PART – E</u> Solid Wastes

Solid Waste		Total Quantity in metric tons		
		During the Previous Financial Year (2022-2023)	During the Current Financial Year (2023-2024)	
(a)	From Process:	Nil		
(b)	From Pollution Control Facilities- Generated			
	a. STP Sludge	NIL	NIL	
	b. Fly Ash	20858	27746.26	
	c. Bottom Ash	1397.65	4058	
(c)	Quantity recycled or re-utilized within the unit			
	a. STP Sludge	NIL	NIL	
	b. Fly Ash	17356.52	27746.26	
	c. Bottom Ash	1397.65	4058	
	2. Sold			
	a. STP Sludge	NIL	NIL	
	b. Fly Ash	NIL	NIL	
	c. Bottom Ash	NIL	NIL	



Chettinad Cement Corporation Pvt Ltd.

Sangem & Kallur (V), Chincholi (T), Gulbarga (D), Karnataka

3. Disposed		
a. STP Sludge	NIL	NIL
b. Fly Ash	NIL	NIL
c. Bottom Ash	NIL	NIL

PART - F

Please specify the characterizations (in terms of composition of quantum) of hazardous as well as solid wastes and indicate disposal practice adopted for both these categories of wastes

N	lame of the Waste	Quantity	Characteristics	Disposal Practice Adopted
(1)	Hazardous Waste Used / Spent Oil (Category No.5.1)	Opening Stock (01.04.2023) : NIL Generation (Apr'23 - Mar'24) : 2.02 KL Consumption (Apr'23 - Mar'24) : 2.02 KL sold to authorized recycler (0.5 KL utilized in-house lubrication) Closing Stock (31.03.2024) : NIL	Waste Oil containing 5000-7000 kcal/Kg of GCV and Less than 5 ppm of Cd+Cr+Ni	Used for lubrication of conveyors, chain blocks and other motors within the Plant.
(2)	Solid Waste Bottom Ash	Opening stock (01.04.2023) : Nil MT Generation (Apr'23 – Mar'24) : 4058 MT Consumption (Apr'23 – Mar'24) : 4058 MT Closing stock (as on 31.03.2024) : 0.00 MT	Solid containing Sio ₂ : 70-80%, Fe ₂ O ₃ : 2-5 % LOI : 4-6 % Al ₂ O ₃ : 18-30%	100% Utilized within the premises (replacement of Boiler bed materials, used as sand for masonry works)
(3)	Solid Waste Fly Ash	Opening stock (as on 01.04.2023): 100 MT Generation (Apr'23 – Mar'24): 27746.26 MT Consumption (Apr'23 – Mar'24): 27746.26 MT Closing stock (as on 31.03.2024): 100 MT	Solid containing SiO ₂ : 25-35%, Fe ₂ O ₃ : 2-3% LOI: 10-15% K ₂ O+Na ₂ O: <1%	100 % of Fly Ash Utilized in Cement production.

Sangem & Kallur (V), Chincholi (T), Gulbarga (D), Karnataka

PART - G

Impact of the pollution abatement measures taken on conservation of natural resources and on the cost of production.

- Air cooled condensers have been installed to reduce water consumption at Captive Power Plant.
- Stack Emissions were controlled by installation of Pollution control equipment's of ESP's and Baghouses.
- Regular monitoring of ambient air quality, stack emissions and effluent quality have been taken up to the evaluate the efficiency of the pollution control systems and control measures of the overall emissions from stack and ambient air.
- As our pollution control equipment's are working with higher efficiency, maximum amount of emissions are recycled thus conserving raw material and reducing dust emission.
- Flyash Generated from CPP and procurement from surrounding Power Plants are being used in the manufacturing of PPC, thus utilizing waste and conserving limestone.

PART - H

Additional measures / investment proposal for environmental protection including abatement of pollution, prevention of pollution

The expenditure toward environmental protection measure during the period April-2023 to March-2024 is given below:

S. No.	Description	Amount (in lakh)
1	Plantation	1.0
2	Env. Monitoring (Plant and Mines)	6.0
3	Technical consultancy charges (Plant and Mines)	5.0
4	Pollution control equipment's maintenance (Plant and Mines)	99.83
	Total	111.83



Chettinad Cement Corporation Pvt Ltd.

Sangem & Kallur (V), Chincholi (T), Gulbarga (D), Karnataka

PART - I

Any other particulars for improving the quality of environment

- **a.** We have full-fledged Environment Department for development of greenbelt, monitoring & maintenance of pollution control equipment and environmental management at site.
- **b.** Regular monitoring is being done for stack emissions, ambient air quality, ambient noise level and ground water quality. Data analysis is being done for further improve of the environment quality of the plant area.
- **c.** Maintenance department is doing regular checking and scheduled maintenance of all the pollution control devices.
- **d.** We have installed Continuous Emission Monitoring System (CEMS) to display the data on CPCB and KSPCB web sites.
- **e.** Domestic waste water generated is being treated in Sewage Treatment Plant (STP) and treated water is being utilized in plantation & gardening.
- **f.** We are maintaining Zero Liquid Discharge (ZLD) from our premises.
- g. Piezometer is constructed for monthly water level monitoring.

h. Integrated Management Systems have been Implemented - ISO 9001, ISO 14001 & OSHAS 45001.

Place: Kallur

Date: 17.09.2024

Name

Designation

K Salkumar

: Unit Head